



**YACHT BOARDING SYSTEMS**

[www.BoardingRamp.com](http://www.BoardingRamp.com)

The **Steady-Plank**<sup>tm</sup> System

## **The STEADI-PLANK™ Precautions!**

- Do not exceed more than three (3) people on The STEADI-PLANK™ Boarding Ramp at the same time.
- Do not connect more than TWO (2) STEADI-PLANK™ Boarding Ramps or STEADI-PLANK™ Boarding Ramp and STEADI-PLANK™ Ramp Extensions together. The total maximum span cannot exceed twelve (20) feet long.
- The surface of The STEADI-PLANK™ Boarding Ramp will get very hot when in direct sunlight. If the surface exceeds 250 degrees F the aluminum skin may delaminate from the core.
- The STEADI-PLANK™ handrail will get very hot when in direct sunlight.
- Make sure that the STEADI-PLANK™ Mounting System and hardware are firmly secured to the vessel or dock and will not pull lose or break free when used.
- Wash the ramp down to remove salt and other dirt.
- Our ramps are not designed to be cantilevered. They must be supported at both ends either with one of our mounting systems, or be resting on a surface or with a supporting "trapeze arrangement" that will support the wight of the ramp with several people on it.

***Unsure about your first step...don't be...Use The STEADI-PLANK™ Boat Boarding Ramp System©!***